

P24506.S02

WHAT IS CLAIMED IS:

1. An image data communication apparatus connected to an image data source and to a network, and transmitting image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message, the image data communication apparatus comprising;

a memory configured to store a default mail address and a mail address of at least one user;

a panel section configured to select the mail address of at least one user other than the default mail address stored in the memory; and

a controller configured to set the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected by the panel section;

the controller being configured to set the mail address of the user selected by the panel section into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected by the panel section, whereby, when an error occurs, the mail address of the user set into the mail from command of the e-mail is utilized as a destination of a mail error message.

2. The image data communication apparatus according to claim 1, wherein the image data source comprises a scanner connected to the image data communication apparatus.

3. The image data communication apparatus according to claim 1, wherein the panel section comprises a personal computer connected to the image data communication apparatus.

4. The image data communication apparatus according to claim 3, wherein the personal computer displays an HTML document for storing the mail address of the user in the memory.

P24506.S02

5. The image data communication apparatus according to claim 1, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

6. The image data communication apparatus according to claim 1, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

7. An image data communication apparatus connected to an image data source and to a network, and transmitting image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message, the image data communication apparatus comprising;

a memory configured to store a default mail address and a mail address of at least one user;

a panel section configured to select the mail address of at least one user other than the default mail address stored in the memory; and

a controller configured to set the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected by the panel section;

the controller being configured to set the mail address of the user selected by the panel section into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected by the panel section, whereby, when an error occurs, a mail error message is returned to the mail address of the user.

8. The image data communication apparatus according to claim 7, wherein the image data source comprises a scanner connected to the image data communication apparatus.

P24506.S02

9. The image data communication apparatus according to claim 7, wherein the panel section comprises a personal computer connected to the image data communication apparatus.

10. The image data communication apparatus according to claim 9, wherein the personal computer displays an HTML document for storing the mail address of the user in the memory.

11. The image data communication apparatus according to claim 7, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

12. The image data communication apparatus according to claim 7, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

13. An image data communication apparatus connected to an image data source and to a network, and transmitting image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message, the image data communication apparatus comprising;

a memory configured to store a default mail address and a mail address of at least one user;

a panel section configured to select the mail address of at least one user other than the default mail address stored in the memory; and

a controller configured to set the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected by the panel section;

the controller being configured to set the mail address of the user selected by the panel section into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected by the panel section,

P24506.S02

whereby, when an error occurs, a mail error message is returned to the mail address of the user, the mail error message indicating an error in one of transmission of the e-mail by the image data communication apparatus and reception of the e-mail by the receiving apparatus.

14. The image data communication apparatus according to claim 13, wherein the image data source comprises a scanner connected to the image data communication apparatus.

15. The image data communication apparatus according to claim 13, wherein the panel section comprises a personal computer connected to the image data communication apparatus.

16. The image data communication apparatus according to claim 15, wherein the personal computer displays an HTML document for storing the mail address of the user in the memory.

17. The image data communication apparatus according to claim 13, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

18. The image data communication apparatus according to claim 13, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

19. An image data communication apparatus connected to a network, the image data communication apparatus comprising:

a transmitter configured to transmit image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message;

a memory configured to store a default mail address and a mail address of at least one user;

P24506.S02

a panel section configured to select the mail address of at least one user other than the default mail address stored in the memory; and

a controller configured to set the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected by the panel section;

the controller being configured to set the mail address of the user selected by the panel section into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected by the panel section, whereby, when an error occurs, the mail address of the user set into the mail from command of the e-mail is utilized as a destination of a mail error message.

20. The image data communication apparatus according to claim 19, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

21. The image data communication apparatus according to claim 19, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

22. An image data communication apparatus connected to a network, the image data communication apparatus comprising:

a transmitter configured to transmit image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message;

a memory configured to store a default mail address and a mail address of at least one user;

a panel section configured to select the mail address of at least one user other than the default mail address stored in the memory; and

P24506.S02

a controller configured to set the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected by the panel section;

the controller being configured to set the mail address of the user selected by the panel section into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected by the panel section, whereby, when an error occurs, a mail error message is returned to the mail address of the user.

23. The image data communication apparatus according to claim 22, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

24. The image data communication apparatus according to claim 22, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

25. An image data communication apparatus connected to a network, the image data communication apparatus comprising:

a transmitter configured to transmit image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message;

a memory configured to store a default mail address and a mail address of at least one user;

a panel section configured to select the mail address of at least one user other than the default mail address stored in the memory; and

a controller configured to set the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected by the panel section;

P24506.S02

the controller being configured to set the mail address of the user selected by the panel section into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected by the panel section, whereby, when an error occurs, a mail error message is returned to the mail address of the user, the mail error message indicating an error in one of transmission of the e-mail by the image data communication apparatus and reception of the e-mail by the receiving apparatus.

26. The image data communication apparatus according to claim 25, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

27. The image data communication apparatus according to claim 25, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

28. A method for controlling an image data communication apparatus connected to an image data source and to a network, and transmitting image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message, a memory storing a default mail address and a mail address of at least one user, the mail address of at least one user being an address other than the default mail address, the method comprising;

setting the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected; and

setting the mail address of the user into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected, whereby, when an error occurs, the mail address of the user set into the

P24506.S02

mail from command of the e-mail is utilized as a destination of a mail error message.

29. The method according to claim 28, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

30. The method according to claim 28, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

31. A method for controlling an image data communication apparatus connected to an image data source and to a network, and transmitting image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message, a memory storing a default mail address and a mail address of at least one user, the mail address of at least one user being an address other than the default mail address, the method comprising;

setting the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected; and

setting the mail address of the user into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected, whereby, when an error occurs, a mail error message is returned to the mail address of the user.

32. The method according to claim 31, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

33. The method according to claim 31, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

34. A method for controlling an image data communication apparatus connected to an image data source and to a network, and transmitting image data attached to an e-mail to a receiving apparatus via the network, the e-mail including a mail from command and a mail message, a memory storing a default mail address and a mail address of at least one user, the mail address of at least one user being an other address than the default mail address, the method comprising;

setting the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected;
and

setting the mail address of the user into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected, whereby, when an error occurs, a mail error message is returned to the mail address of the user, the mail error message indicating an error in one of transmission of the e-mail by the image data communication apparatus and reception of the e-mail by the receiving apparatus.

35. The method according to claim 34, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

36. The method according to claim 34, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

37. A method for controlling an image data communication apparatus connected to a network, and transmitting image data attached to an e-mail, the e-mail including a mail from command and a mail message, a memory storing a default mail address and a mail address of at least one user, the mail address of at least user being an address other than the default mail address, the method comprising:

P24506.S02

setting the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected;

setting the mail address of the user into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected, whereby, when an error occurs, the mail address of the user set into the mail from command of the e-mail is utilized as a destination of a mail error message; and

transmitting the image data attached to the e-mail to a receiving apparatus via the network.

38. The method according to claim 37, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

39. The method according to claim 37, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

40. A method for controlling an image data communication apparatus connected to a network, and transmitting image data attached to an e-mail, the e-mail including a mail from command and a mail message, a memory storing a default mail address and a mail address of at least one user, the mail address of at least one user being an address other than the default mail address, the method comprising:

setting the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected;

setting the mail address of the user into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected, whereby, when an error occurs, a mail error message is returned to the mail address of the user; and

P24506.S02

transmitting the image data attached to the e-mail to a receiving apparatus via the network.

41. The method according to claim 40, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

42. The method according to claim 40, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.

43. A method for controlling an image data communication apparatus connected to a network, and transmitting image data attached to an e-mail, the e-mail including a mail from command and a mail message, a memory storing a default mail address and a mail address of at least one user, the mail address of at least one user being an address other than the default mail address, the method comprising:

setting the default mail address into the mail from command of the e-mail to which the image data is attached when the mail address of the user is not selected;

setting the mail address of the user into the mail from command of the e-mail to which the image data is attached when the mail address of the user is selected, whereby, when an error occurs, a mail error message is returned to the mail address of the user, the mail error message indicating an error in one of transmission of the e-mail by the image data communication apparatus and reception of the e-mail by the receiving apparatus; and

transmitting the image data attached to the e-mail to a receiving apparatus via the network.

44. The method according to claim 43, wherein the image data attached to the e-mail is converted into a format for e-mail transmission.

P24506.S02

45. The method according to claim 43, wherein the default mail address is pre-stored in the memory and the mail address of the user is stored in the memory by the user.